



videosecurity



Features

- Easy to install, plug and play
- Perform remote surveillance on network
- Embedded Web Server
- Multi user and secure password protection
- Auto white balance (AWB) & auto tracing white balance for color temperatures from 2500°k to 9500°k.
- Advanced motion detection multi-zone & multi-sensitivity
- Privacy image masking with free position and size
- CIF up to Full D1 resolution
- Fixed shutter speed: 1/1000 sec.
- Low Lux: By employing high sensitivity image sensor and low noise circuit design produces 0.5 lux
- Supports the SD card as a local storage
- USB interface for setup
- Real-time and synchronized A/V stream
- No latency. Synchronized Analog/ Digital signal
- Supports the MDIX protocol. Recognizes both the normal and crossover cables, either of which can connect up with a LAN camera.



videosecurity



Specifications

MODEL	SKK-3312F LAN
Image Device	1/3" Sony Super HAD CCD
Picture Elements	752(H) x 582(V)
Horizontal Resolution	480 TV Lines
Network Throughout	2.4 Mbytes/ sec
Video Output	1.0Vpp, 75 Ohm, composite
Audio	16bit, 8 kHz sample rate
Microphone	Built-in
Auto White Balance	2500°K ~ 9,500°K
Fixed Shutter	1/1000 sec
Auto Electronic Shutter	1/50 ~ 1/100000 sec
Sensitivity	0.5 lux/ F1.2
Auto Iris Type	DC-iris
Mirror Function	Yes
Flicker Less	Yes
Privacy Zone Masking	3 Areas
Video Fine Tune	Max AGC Gain, Contrast, Brightness, BLC, Sharpness, Saturation, Fluorescent
Compression	MJPEG/ MPEG4
MJPEG Performance	Up to 25 frames/ sec
MJPEG Picture Size	4 ~ 64 KB
MJPEG Watermark	Digital Signature
MJPEG Motion Detection	Advanced MD (96 zone, 5 levels sensitivity)
MPEG4 Resolution	Full D1, Half D1, CIF
MPEG4 Quality	5 Fixed Levels and Customized Bitrate (From 64Kbps to 8Mbps)
MPEG4 Framerate	30, 24, 15 fps at all resolution
SD Socket	Yes
RS-232	Yes
Network Interface	Ethernet (RJ-45Wired, 10/100 Base-TX), MDIX support
Network Protocol	TCP/ IP, DHCP, HTTP, UDP, SNTP, ICMP, DDNS, DNS, UpnP, (FTP/SMTP only in MJPEG mode)
Alarm I/O	Yes
USB Interface	Yes
Secure Password	Multi-level/ Multi-user
Software Upgrade	Upgrade via SD Card, RS-232, USB or FTP
Power Input	5V DC/ 2A
Operation Environment	Requires proper enviromental housing for outdoor use
Weigh	306g
Dimensions	62 (W) x 50 (H) x 95 (D) mm
Operation Temperature	5°C ~ 50°C
Regulation	FCC,CE

Specifications subject to change without notice



- *Integration of functional remote monitoring software application.
- *16 channel IP media streaming recording and monitoring.
- *Various viewing modes of split-screen.
- *The notification of instant alarm and screen warning.
- *PTZ camera support.
- *Functional recording setting: recycle recording / event triggered recording / pre-alarm recording and flexible recording storage.
- *Programmable recording schedule setting more flexible.
- *Functional playback software: various speed playback, frame stepping, alarm searching, AVI / JPEG backup, fast-move playback, and instant alarm file searching.